

KOHLNSTOFF[®] COLORX 13

Speciality Carbon Black

Product Description

COLORX 13 is a medium structure regular color specialty carbon black. Highly suitable for printing ink and other color applications. It provides ease of dispersion and improved flow properties.

Application

- Suitable for web offset and coldest printing ink
- General dispersions in adhesives and sealants
- Suited for concrete and cement application

Test	ASTM Test Method	Units	Typical Value
BET Surface Area	D-6556	(m ² /gm)	75
Oil Absorption No. (OAN)	D-2414	(cc/100 g)	103
Tint Strength	D-3265	%	103
Sieve Residue # 325	D-1514	ppm	<50
Heating Loss (as packed)	D-1509	%	<3

Packaging

- Product Form: Powder
- Regional Availability: Global
- Bag Packaging Options: 10 & 20 kg paper bags

Disclaimer:

This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and Himadri Speciality Chemical Ltd. disclaims all warranties express or implied, including merchantability or fitness for a particular purpose as to (i) such information, (ii) any product or (iii) intellectual property infringement. In no event is Himadri Speciality Chemical Ltd. responsible for, and does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.

Corporate Office: Ruby House, 8, India Exchange Place, 2nd Floor, Kolkata –700 001, West Bengal, India
Tel: +91 33 2230 4363 | E-mail: carbonblack@himadri.com | Web: www.himadri.com