

KOHLNSTOFF[®] COLORX 34

Speciality Carbon Black

Product Description

COLORX 34 is a high color intensity specialty carbon black in powder form offers high color intensity, excellent jetness and high tinting strength property. It's a easy to disperse black offers high color intensity due to its ease of dispersion.

Application

- Used as decorative coating
- Suitable for adhesives and sealants
- Applicable in general dispersions

The disperse ability of COLORX 34 depends on the formulation & equipment's used.

Test	ASTM Test Method	Units	Typical Value
BET Surface Area	D-6556	(m ² /gm)	118
Oil Absorption No. (OAN)	D-2414	(cc/100 g)	125
Tint Strength	D-3265	%	120
Sieve Residue # 325	D-1514	ppm	<50
Heating Loss (as packed)	D-1509	%	<3

Packaging

- Product Form: Powder
- Regional Availability: Global
- Bag Packaging Options: 10 & 20 kg paper bags

Disclaimer:

This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and Himadri Speciality Chemical Ltd. disclaims all warranties express or implied, including merchantability or fitness for a particular purpose as to (i) such information, (ii) any product or (iii) intellectual property infringement. In no event is Himadri Speciality Chemical Ltd. responsible for, and does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.

Corporate Office: Ruby House, 8, India Exchange Place, 2nd Floor, Kolkata –700 001, West Bengal, India
Tel:+91 33 2230 4363 | E-mail: carbonblack@himadri.com | Web: www.himadri.com