

KLAREX RG 315 Speciality Carbon Black

Product Description

Himadri's **KLAREX RG 315** is suitable for extruded rubber applications with good dynamic properties and low heat build-up. It is easy to disperse and exhibits good extrudability. It is equivalent to ASTM N650 in compound mechanical properties with superior cleanliness.

Product Features

- Superior cleanliness
- Excellent dispersibility
- Good extrudability

Applications

- Critical extrusion compounds
- Applications such as weather stripping, hoses and profiles

Typical Values

	ASTM Test Method	Units	Typical Value
I ₂ No.	D-1510	(g/kg)	36
Oil Absorption No. (OAN)	D-2414	(cc/100 g)	122
Tint (ITRB #3)	D-3265	%	53
S.R # 325	D-1514	ppm	≤15
Heating Loss (as packed)	D-1509	%	<0.5
Fines	D-1508	%	<12 (PB) <8 (JB)
Ash	D-1506	%	<0.2

Packaging

Bag Packaging Options: 25 kg polyethylene lined paper bags

Bulk Packaging Options: 1000/500 kg flexible intermediate bulk containers (FIBC)

Product Technical Data Sheet
KOHLENSTOFF® Carbon Blacks



Contact Information

2nd Floor, Ruby House,
8, India Exchange Place
Kolkata – 700001, India
+91 33 2230 9051/ 2230 4363

Disclaimer

This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and Himadri Speciality Chemical Ltd. disclaims all warranties express or implied, including merchantability or fitness for a particular purpose as to (i) such information, (ii) any product or (iii) intellectual property infringement. In no event is Himadri Speciality Chemical Ltd. responsible for, and does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.