

Anthracene Oil Specifications :

| SL. NO. | TEST PARAMETERS | UNIT | TEST METHODS | ANTHRACENE OIL SPECIFICATIONS |
|---------|----------------------------------|----------------|---------------------------------------|-------------------------------|
| 2 | Sp.Gr. at 15.5 ^o C | ~ | IS : 1202 - 1978 | 1.07 to 1.15 |
| 3 | BMCI | ~ | In-house | 150 min. |
| 4 | Ashphaltene Content | %w/w | IS:1448 [P:22] - 1985 | Nil |
| 5 | n-Pentane Ins. | %w/w | ASTM D-893 | 7.0 max. |
| 6 | Sulphur | %w/w | IS : 1448 [P:33] - 1991 (Refmd. 2003) | 0.5 max. |
| 7 | Sodium | ppm | By AAS | 25 max. |
| 8 | Calorific Value | Cal/gm | IS : 1448 [P:6] - 1984 | 9000 min. |
| 9 | Flash Point (PMCC) | ^o C | IS : 1448 [P:21] - 1992 (Refmd. 2003) | 150 min. |
| 10 | Viscosity at 98.9 ^o C | sus | ASTM D-88 - 81 (1987) | 50 max. |
| 11 | Carbon Residue | %w/w | IS : 1448 [P:8] - 1967 (Refmd. 2003) | 1.0 max. |