

ENERGEX Li⁺8536S

Conductive Carbon

Product Description

Li⁺8536 S conductive carbon black contains ultra-high structure specially designed for conductive coating and other conductive applications. The high structure of this carbon black provides excellent dispersibility and superior cycling efficiency. These unique features of this product make as an ideal choice for high-density applications and prolonged cycle operations for lithium ion battery.

Product Features

- High Structure
- High Conductivity
- Excellent dispersibility

Applications

- Automatic EV, Li-ion battery
- Stationary storage
- ESD or other conductive coating application

Test	ASTM Test Method	Units	Typical Range
Moisture	D-1509	%	<0.5
BET surface area	D-6556	m ² /g	60-70
Oil Absorption No. (OAN)	D-2414	(cc/100 g)	210-230
Sieve Residue # 325	D-1514	ppm	<10
Iron Content	ITM*	ppm	<15

*Internal Test Method (AAS)

Packaging

- Product Form: Available in Powder form.
- Regional Availability: Global
- Bag Packaging Options: 10 kg paper bags

Disclaimer:

This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and Himadri Speciality Chemical Ltd. disclaims all warranties express or implied, including merchantability or fitness for a particular purpose as to (i) such information, (ii) any product or (iii) intellectual property infringement. In no event is Himadri Speciality Chemical Ltd. responsible for, and does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.

Corporate Office: Ruby House, 8, India Exchange Place, 2nd Floor, Kolkata –700 001, West Bengal, India

Tel: +91 33 2230 4363 | E-mail: carbonblack@himadri.com | Web: www.himadri.com