

KOHLLENSTOFF® COLORX 93

Speciality Carbon Black

Product Description

COLORX 93 is a general purpose high color pigment black. This high surface area and low structure specialty black provides excellent jetness, good UV durability and a better blue undertone. Its small particle size also promotes UV energy adsorption for good exterior durability

Application

- Recommended to use in industrial and architectural coatings.
- Used as color dispersion for leather application.

The disperse ability of COLORX 93 depends on the formulation & equipment's used.

| Test | ASTM Test Method | Units | Typical Value |
|--------------------------|------------------|----------------------|---------------|
| BET Surface Area | D-6556 | (m ² /gm) | 250 |
| Oil Absorption No. (OAN) | D-2414 | (cc/100 g) | 58 |
| Tint Strength | D-3265 | % | 145 |
| Sieve Residue # 325 | D-1514 | ppm | <50 |
| Heating Loss (as packed) | D-1509 | % | <3 |

Packaging

- Product Form: Powder
- Regional Availability: Global
- Bag Packaging Options: 10 & 20 kg paper bags

Disclaimer:

This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and Himadri Speciality Chemical Ltd. disclaims all warranties express or implied, including merchantability or fitness for a particular purpose as to (i) such information, (ii) any product or (iii) intellectual property infringement. In no event is Himadri Speciality Chemical Ltd. responsible for, and does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.